

Missing=Blank state

	page	Model/Series	Contents	Incorrect	Correct	
Guidance	013	High speed·High accuracy 3-axis sensor	Output	Tilt θy	Tilt θx	
Motorized Stage	1-022	PG413	Motor model#	PK525HPB-C15	PK523HPB-C15	
	1-024	PG413	Motor model#	PK525HPB-C15	PK523HPB-C15	
	1-025	PG series	Comment	Loadcapacity 3kgf	Loadcapacity 5kgf	
	1-026	PG430	Motor model#	PK525HPB-C15	PK523HPB-C15	
	1-028	PG430	Motor model#	PK525HPB-C15	PK523HPB-C15	
	1-037	PG series	Motor model#	PK525HPB-C15	PK523HPB-C15	
	1-052	KXG Series	Color of Sensor cable	Orange/Black	Orange/Black dot	
	1-052	KXG Series	Color of Sensor cable	Orange/Red	Orange/Red dot	
	1-052	KXG Series	Color of Sensor cable	Gray/Black	Gray/Black dot	
	1-052	KXG Series	Color of Sensor cable	Gray/Red	Gray/Red dot	
	1-052	KXG Series	Color of Sensor cable	White/Black	White/Black dot	
	1-052	KXG Series	Color of Sensor cable	White/Red	White/Red dot	
	1-087	KZC04015	Lost motion	2μm	1μm	
	1-087	KXL Series	Color of Sensor cable	Orange/Black	Orange/Black dot	
	1-087	KXL Series	Color of Sensor cable	Orange/Red	Orange/Red dot	
	1-087	KXL Series	Color of Sensor cable	Gray/Black	Gray/Black dot	
	1-087	KXL Series	Color of Sensor cable	Gray/Red	Gray/Red dot	
	1-087	KXL Series	Color of Sensor cable	White/Black	White/Black dot	
	1-087	KXL Series	Color of Sensor cable	White/Red	White/Red dot	
	1-091	KX04/06	Connector model#	HR10A-10P-12S	HR10A-10J-12P	
	1-117	KHC series	Slit origin sensor	Installed	-	
	1-119	KHC series	Motor frame size	□38mm	□28mm	
		1-120	KHC series	Timing chart errors	The origin end face/Stroke center 1.5 Opposite end face 0	Opposite end face 1.5 The origin end face/Stroke center 0
		1-141	KGB06050	MAX speed	10.5°/sec[15kHz]	31.5°/sec[15kHz]
		1-141	KGB06075	MAX speed	7°/sec[15kHz]	21°/sec[15kHz]
		1-141	KGB06075	MAX speed	5.5°/sec[15kHz]	16.5°/sec[15kHz]
		1-141	KGB06125	MAX speed	4.5°/sec[15kHz]	13.5°/sec[15kHz]
		1-141	KAB06050	MAX speed	Upper:10.5°/sec[15kHz] Lower:7°/sec[15kHz]	Upper:31.5°/sec[15kHz] Lower:21°/sec[15kHz]
		1-141	KAB06075	MAX speed	Upper:7°/sec[15kHz] Lower:5.5°/sec[15kHz]	Upper:21°/sec[15kHz] Lower:16.5°/sec[15kHz]
		1-141	KAB06100	MAX speed	Upper:5.5°/sec[15kHz] Lower:4.5°/sec[15kHz]	Upper:16.5°/sec[15kHz] Lower:13.5°/sec[15kHz]
		1-142	KGB06-L series	Width direction/mounting pitch	70/40/30	73/50/32
		1-143	KGB06050	Timing chart CCW specs[dig]	10.5	8.7
		1-143	KGB06075	Timing chart CCW specs[dig]	8.3	5.7
		1-143	KGB06100	Timing chart CCW specs[dig]	6.3	5.2
		1-143	KGB06125	Timing chart CCW specs[dig]	5.2	4.2
		1-150	KGW04-L	Bolt hole size	φ8	φ6
		1-171	KRB04/06	Sensor model#	PM-R24 (SUNX)	EE-SX4134 (Omuron Co.,Ltd.)
		1-181	KS402-100-5	Screw size	4 of M6 – 15	4 of M6 – 16
		1-185	KRE10360	Model# on specification	KRE10360-C	KRE10360
		1-185	KRE10360	spec	Not shown	Provided screw (Hexagon-headed bolt) 4 of M6 – 16
		1-185	KRE10360	spec	Back Rush	Back lash
		1-186	KRE10360	Hole size	8-Mφ4 DP6 (※1)	8-M4 DP6
		1-191	KS451	ectrical Specification:Notes for Moto	See page P.1-213~ for details of single motor specification.	Delete
		1-193	Motorized Stage Unit	Z axis of 6 axis unit	KH0604-L	KHC06004F-5
		1-118	KHC06004F	Dimensional outline drawings	4-M3 6DP	4-M3 4DP
	1-118	KHC07004F	Dimensional outline drawings	4-M3 6DP	4-M3 4DP	
	1-120	KHC06004F	Timing chart errors	Timing chart diagram numeric error	Opposite end face 1.5, The origin end face·Stroke center	
	1-120	KHC07004F	Timing chart errors	Timing chart diagram numeric error	Opposite end face 1.5, The origin end face·Stroke center	
Manual Stage	2-040	BSS23-60C	Dimension line	End face of the stage	Center of the tapped hole	
	2-043	BYT04013	Loadcapacity	95.6N	96N	
	2-043	BYT06013	Loadcapacity	191.6N	192.1N	
	2-047	BSS26-40AR	SPEC/Model	BSB26-40AR	BSS26-40AR	
	2-074	B23-40 series	BORE Hole	5.5mm	7.0mm	
	2-082	B33 series	Allowablemomentload:Pitch	Pitch Value	Roll Value	
	2-082	B33 series	Allowablemomentload:Yaw	Yaw Value	Pitch Value	
	2-082	B33 series	Allowablemomentload:Roll	Roll Value	Yaw Value	
	2-082	B33 series	Momentstiffness:Pitch	Pitch Value	Roll Value	
	2-082	B33 series	Momentstiffness:Yaw	Yaw Value	Pitch Value	
	2-082	B33 series	Momentstiffness:Roll	Roll Value	Yaw Value	
	2-094	B35	Travel distance per rotation of knob	3mm	approx.5mm	
	2-094	B35-N	Travel distance per rotation of knob	2mm	approx.3mm	
	2-102	B05-41NM/B05-41NRM	Add the thickness dimension	Not shown	29mm	
	2-102	B05-1NHM	φ6 C'BORE Depth on the dimensional drawing	10.5DP	9DP	
	2-133	B09-47L	spec/Allowable load for moment/Pitch	2.0N	1.3N	
2-133	B09-47L	spec/Allowable load for moment/Roll	2.0N	1.3N		
Optics						
	A-016	SX20 Series	Total Mass/Rail Length L	0.71	0.7	
	A-022	SX20 Series	Total Mass/standard	0.71	0.7	
	A-018	SX30, SX45 Series	Maintenance	Cartridge Grease	Alvania Grease	
	A-019	SX15 Series	Physical Dimensions	32.6	31.6	
	A-019	SX15 Series	Physical Dimensions	32.6	31.6	
	A-021	SX20 Series	Physical Dimensions	45.6	44.6	
	A-021	SX20 Series	Physical Dimensions	45.6	44.6	
	A-025	SX26 Series	Physical Dimensions	63	62	
	A-025	SX26 Series	Physical Dimensions	63	62	
	A-029	SX30 Series	Physical Dimensions	47.5	46.5	
	A-029	SX30 Series	Physical Dimensions	73	72	

Missing=Blank state

	page	Model/Series	Contents	Incorrect	Correct
Single Axis Actuator	A-029	SX30 Series	Physical Dimensions	47.5	46.5
	A-029	SX30 Series	Physical Dimensions	73	72
	A-031	E3040	Dimension from the center of screw to the end face	15	14.5
	A-031	T3060	Size of depth on motor side	2	2.5
	A-032	SX30	Physical Dimensions	For L=250, 350, 450, 550 mounting of sensor rail is enabled only in the direction shown on the above drawing.	Delete
	A-033	SX45 Series	Physical Dimensions	65.5	68.1
	A-033	SX45 Series	Physical Dimensions	103	105.6
	A-033	SX45 Series	Physical Dimensions	65.5	68.1
	A-033	SX45 Series	Physical Dimensions	103	105.6
	A-036	SX45	Physical Dimensions	For L=390, 490, 590, mounting of sensor rail is enabled only in the direction shown on the above drawing.	Delete
Optical Fiber Alignment	4-021	ES5201	Not shown Z-axis specification		Will be added
	4-023	ES6201/ES6211/ES6221	Not shown Z-axis specification		Will be added
	4-054	VSTC-620CCSET	Model	VSTC-620CCSET	VSTC-620PWCSET
	4-055	VMEGA Series	Discon		Delete
	4-056	VSTP Series	Model	VSTP-1210D	VSTP-1210D-A
	4-056	VSTP Series	Model	VSTP-1230D	VSTP-1230D-A
	4-056	VSTP-1210D-A	Output power	(1CH max. load 10W)	10W(1CH max. load 10W)
	4-056	VSTP-1230D-A	Output power	(1CH max. load 30W)	30W(1CH max. load 30W)
4-60	MPU series	spec	Not shown	add Weight	
	5-054	H400-C050/K12	Tilt stage	HB10	HB11
	5-054	H400-C100/K12	Tilt stage	HB10	HB11
	5-054	H400-C150/K12	Tilt stage	HB10	HB11
	5-054	H400-C200/K12	Tilt stage	HB10	HB11
	5-054	H400-C050/K55	Tilt stage	HB10	HB11
	5-054	H400-C100/K55	Tilt stage	HB10	HB11
	5-054	H400-C150/K55	Tilt stage	HB10	HB11
	5-054	H400-C200/K55	Tilt stage	HB10	HB11
	5-054	H400-C050/K12E	Tilt stage	HB10	HB11
	5-054	H400-C100/K12E	Tilt stage	HB10	HB11
	5-054	H400-C150/K12E	Tilt stage	HB10	HB11
	5-054	H400-C200/K12E	Tilt stage	HB10	HB11
	5-054	H400-C050/K55E	Tilt stage	HB10	HB11
	5-054	H400-C100/K55E	Tilt stage	HB10	HB11
	5-054	H400-C150/K55E	Tilt stage	HB10	HB11
	5-054	H400-C200/K55E	Tilt stage	HB10	HB11
	5-065	Pinhole	Comment		※3 Φ0.5 type : Not available H350B/R-C050.
INDEX	INDEX-018	DS100-LINK2-0.5	Clerical errors	DS100LINK2-0.5	DS100-LINK2-0.5
	INDEX-018	DS100-LINK3-0.5	Clerical errors	DS100LINK3-0.5	DS100-LINK3-0.5
	INDEX-020	KS402-75-5	Index	1-177	1-181
	INDEX-021	KS402-100-5	Index	1-177	1-181
	INDEX-022	KS402-180-5	Index	1-177	1-181

Disclaimers The information on this web site ensures the accuracy of the information, but makes no warranty as to the accuracy, completeness or suitability. The Company cannot be held liable or responsible for any damage caused as a result of using the Site or for not being able to use the Site. The information on the website may be changed without prior notification and without incurring any obligation or liability for us. The operation of this website may also be suspended or stopped at any time without prior notice.